

## Fishing Vessel (Factory Trawler)

**General:** Laid out as a modern freezing trawler with two continuous decks and a partly covered

upper deck, this trawler is intended to work as a single otter board and/or pair trawler for both bottom and/or mid-water trawling. The hold and engine room are located under the first deck which, in turn, holds the fish processing area. The trawl handling winches and other equipment are found on the second deck along with crew accommodation,

which also extends into the superstructure.

Main Particulars: Length o.a. 50.00 m

Length p.p.48.00 mBreadth11.25 mDepth, factory deck4.50 mDepth, trawl deck7.00 mDraught, design4.45 mDraught, scantling5.00 m

Capacity: Hold Volume 700 m<sup>3</sup>

 $\begin{array}{ccc} \text{Factory deck area} & 300 \text{ m}^2 \\ \text{Receiving bin volume} & 2 \text{ x } 30 \text{ m}^3 \\ \text{Fuel} & 250 \text{ m}^3 \\ \text{Fresh water} & 50 \text{ m}^3 \end{array}$ 

Silage, etc. 80 m³
Number of single cabins: 6
Number of double cabins: 8
Hospital, with 2 beds: 1

Speed: Service speed 12.00 kn

Propeller optimized for 5 kn (towing speed)

Machinery and Alt 1 Traditional Diesel Engine via reduction gear Equipment: Alt 2 Diesel Electric

Alt 2 Diesel Electric
Alt 3 Hybrid (traditional D. E. with electric PTO/PTI)

Propulsion power, about 1,500 kW

Propeller CP, Ø-3500 mm in nozzle Propeller (alt) 2 azimuths in nozzles

El-power engines (apart from propulsion) 2 x 500 kW

Miscellaneous: Class designation DNV, Fishing Vessel, Stern Trawler

Option Ice C, Clean

**Ref. No.:** KEH 1288

